



**NOW ALSO WITH A WLL OF 22 AND 30 TON**



## SMOOTH OPERATOR

The Green Pin® Snatch Block S is a light-weight snatch block type 601S with a Green Pin® Shackle attached. All sizes of the Green Pin® Snatch Block S have a smooth, uninterrupted pull due to conical roller bearings. Its coating ensures long-term durability, even under harsh conditions. The Green Pin® Snatch Block S is available in a range with a working load limit from 2 up to 30 ton.

For more information please contact [sales@vanbeest.nl](mailto:sales@vanbeest.nl)

[greenpin.com](http://greenpin.com)

A VAN BEEST BRAND



## Product update

April 2018

### Green Pin® Snatch Block S

**Product code:** P-6951  
**Material:** Carbon steel, fitted with conical roller bearings  
**Safety Factor:** MBL equals 4 x WLL  
**Finish:** Painted  
**Certification:** **2.1** **2.2** **MTC<sup>b</sup>** **CE**  
**Note:** Working Load Limit is on the headfitting

| working load limit | diameter wire rope | diameter outside sheave | length | width | width outside | weight each |
|--------------------|--------------------|-------------------------|--------|-------|---------------|-------------|
| t                  | mm                 | a mm                    | b mm   | c mm  | d mm          | kg          |
| 2                  | 7-9                | 75                      | 293    | 75    | 82            | 3.9         |
| 4                  | 10-12              | 115                     | 363    | 102   | 120           | 6.4         |
| 4                  | 12-14              | 152                     | 417    | 102   | 160           | 8.4         |
| 8                  | 14-16              | 152                     | 477    | 118   | 160           | 14.3        |
| 12                 | 14-16              | 152                     | 555    | 147   | 160           | 20          |
| 8                  | 20-22              | 152                     | 477    | 118   | 160           | 14.1        |
| 12                 | 20-22              | 152                     | 555    | 147   | 160           | 20          |
| 15                 | 24-26              | 152                     | 585    | 162   | 160           | 24          |
| 4                  | 10-12              | 203                     | 478    | 102   | 210           | 11          |
| 12                 | 14-16              | 203                     | 580    | 147   | 210           | 27          |
| 8                  | 20-22              | 203                     | 526    | 118   | 210           | 18          |
| 12                 | 20-22              | 203                     | 580    | 147   | 210           | 28          |
| 15                 | 24-26              | 203                     | 646    | 162   | 210           | 30          |
| 8                  | 14-16              | 254                     | 582    | 118   | 260           | 26          |
| 8                  | 20-22              | 254                     | 582    | 118   | 260           | 26          |
| 12                 | 20-22              | 254                     | 680    | 147   | 260           | 35          |
| 15                 | 24-26              | 254                     | 705    | 162   | 260           | 42          |
| 8                  | 20-22              | 305                     | 612    | 118   | 310           | 31          |
| 12                 | 20-22              | 305                     | 745    | 147   | 310           | 53          |
| 15                 | 24-26              | 305                     | 771    | 162   | 310           | 55          |
| 8                  | 20-22              | 357                     | 662    | 118   | 360           | 31          |
| 12                 | 20-22              | 357                     | 770    | 147   | 360           | 60          |
| 15                 | 24-26              | 357                     | 798    | 162   | 360           | 63          |
| 22                 | 28-32              | 357                     | 906    | 216   | 385           | 126         |
| 8                  | 20-22              | 406                     | 712    | 118   | 410           | 35          |
| 12                 | 20-22              | 406                     | 820    | 147   | 410           | 67          |
| 15                 | 24-26              | 406                     | 848    | 162   | 410           | 70          |
| 22                 | 28-32              | 406                     | 963    | 216   | 415           | 139         |
| 8                  | 20-22              | 457                     | 762    | 118   | 460           | 42          |
| 12                 | 20-22              | 457                     | 878    | 147   | 460           | 75          |
| 15                 | 24-26              | 457                     | 898    | 162   | 460           | 78          |
| 22                 | 28-32              | 457                     | 1033   | 216   | 465           | 154         |
| 30                 | 28-32              | 457                     | 1083   | 238   | 468           | 218         |



[greenpin.com](http://greenpin.com)

A VAN BEEST BRAND



**NOW ALSO WITH A WLL OF 22 AND 30 TON**



## SMOOTH OPERATOR

The Green Pin® Snatch Block S is a light-weight snatch block type 601S with a Green Pin® Shackle attached. All sizes of the Green Pin® Snatch Block S have a smooth, uninterrupted pull due to conical roller bearings. Its coating ensures long-term durability, even under harsh conditions. The Green Pin® Snatch Block S is available in a range with a working load limit from 2 up to 30 ton.

For more information please contact [sales@vanbeest.nl](mailto:sales@vanbeest.nl)

[greenpin.com](http://greenpin.com)

A VAN BEEST BRAND



## Product update

April 2018

### Green Pin® Snatch Block S

**Product code:** P-6951  
**Material:** Carbon steel, fitted with conical roller bearings  
**Safety Factor:** MBL equals 4 x WLL  
**Finish:** Painted  
**Certification:** **2.1** **2.2** **MTC<sup>b</sup>** **CE**  
**Note:** Working Load Limit is on the headfitting

| working load limit | diameter wire rope | diameter outside sheave | length   | width   | width outside | weight each |
|--------------------|--------------------|-------------------------|----------|---------|---------------|-------------|
| t                  | inch               | a inch                  | b inch   | c inch  | d inch        | lbs         |
| 2                  | 9/32 - 3/8         | 3                       | 11 9/16  | 3       | 3 1/4         | 8.60        |
| 4                  | 3/8 - 1/2          | 4 1/2                   | 14 9/32  | 4       | 4 23/32       | 14.11       |
| 4                  | 1/2 - 9/16         | 6                       | 16 7/16  | 4       | 6 9/32        | 18.52       |
| 8                  | 9/16 - 5/8         | 6                       | 18 25/32 | 4 5/8   | 6 9/32        | 31.5        |
| 12                 | 9/16 - 5/8         | 6                       | 21 7/8   | 5 25/32 | 6 9/32        | 44.1        |
| 8                  | 3/4 - 7/8          | 6                       | 18 25/32 | 4 5/8   | 6 9/32        | 31.1        |
| 12                 | 3/4 - 7/8          | 6                       | 21 7/8   | 5 25/32 | 6 9/32        | 44.1        |
| 15                 | 1                  | 6                       | 23 1/32  | 6 3/8   | 6 9/32        | 52.9        |
| 4                  | 3/8 - 1/2          | 8                       | 18 13/16 | 4       | 8 9/32        | 24.3        |
| 12                 | 9/16 - 5/8         | 8                       | 22 13/16 | 5 25/32 | 8 9/32        | 59.5        |
| 8                  | 3/4 - 7/8          | 8                       | 20 23/32 | 4 5/8   | 8 9/32        | 39.7        |
| 12                 | 3/4 - 7/8          | 8                       | 22 13/16 | 5 25/32 | 8 9/32        | 61.7        |
| 15                 | 1                  | 8                       | 25 7/16  | 6 3/8   | 8 9/32        | 66.1        |
| 8                  | 9/16 - 5/8         | 10                      | 22 29/32 | 4 5/8   | 10 1/4        | 57.3        |
| 8                  | 3/4 - 7/8          | 10                      | 22 29/32 | 4 5/8   | 10 1/4        | 57.3        |
| 12                 | 3/4 - 7/8          | 10                      | 26 3/4   | 5 25/32 | 10 1/4        | 77.2        |
| 15                 | 1                  | 10                      | 27 3/4   | 6 3/8   | 10 1/4        | 92.6        |
| 8                  | 3/4 - 7/8          | 12                      | 24 3/32  | 4 5/8   | 12 3/16       | 68.3        |
| 12                 | 3/4 - 7/8          | 12                      | 29 5/16  | 5 25/32 | 12 3/16       | 116.8       |
| 15                 | 1                  | 12                      | 30 5/16  | 6 3/8   | 12 3/16       | 121.3       |
| 8                  | 3/4 - 7/8          | 14                      | 26 1/32  | 4 5/8   | 14 5/32       | 68.3        |
| 12                 | 3/4 - 7/8          | 14                      | 30 9/32  | 5 25/32 | 14 5/32       | 132.3       |
| 15                 | 1                  | 14                      | 31 3/8   | 6 3/8   | 14 5/32       | 138.9       |
| 22                 | 1 1/8 - 1 1/4      | 14                      | 35 21/32 | 8 1/2   | 15 5/32       | 277.8       |
| 8                  | 3/4 - 7/8          | 16                      | 27       | 4 5/8   | 16 5/32       | 77.2        |
| 12                 | 3/4 - 7/8          | 16                      | 32 9/32  | 5 25/32 | 16 5/32       | 147.7       |
| 15                 | 1                  | 16                      | 33 3/8   | 6 3/8   | 16 5/32       | 154.3       |
| 22                 | 1 1/8 - 1 1/4      | 16                      | 37 29/32 | 8 1/2   | 16 11/32      | 306.5       |
| 8                  | 3/4 - 7/8          | 18                      | 29 31/32 | 4 5/8   | 18 1/8        | 92.6        |
| 12                 | 3/4 - 7/8          | 18                      | 34 9/16  | 5 25/32 | 18 1/8        | 165.3       |
| 15                 | 1                  | 18                      | 35 11/32 | 6 3/8   | 18 1/8        | 172.0       |
| 22                 | 1 1/8 - 1 1/4      | 18                      | 40 21/32 | 8 1/2   | 18 5/16       | 339.5       |
| 30                 | 1 1/8 - 1 1/4      | 18                      | 42 5/8   | 9 3/8   | 18 7/16       | 480.6       |



[greenpin.com](http://greenpin.com)

A VAN BEEST BRAND